





LCD with real-time information:

- Grease meter
- Grease level gauge
- Battery capacity gauge

Two flow rates:

- High 6 oz/min (170 g/min)
- Low 4 oz/min (113 g/min)

15 grease cartridges per battery charge



Durable & Efficient

- Ball and needle bearings
- Curved slot yoke optimizes mechanical efficiency
- Case-hardened piston for wear and bend resistance
- Impact-resistant LCD lens surrounded by impactabsorbing bezel

Convenient

• LED flashlight with on/off control



Patented Airflow Management

Optimizes motor and transmission life



Ergonomic

LEMITE°

- Shape, weight and balance designed for less physical strain
- Soft, comfortable grip



Multi-function LCD

LCD and Icons Keep You in Control

Button resets functions, turns flashlight on or off and toggles between ounces and grams



Switch allows you to choose between two flow rates



Display turns red during stall condition



Display flashes red when the gun loses prime or runs out of grease



Battery level flashes to signify low voltage



Grease level flashes when low grease condition occurs





Specifications

Model Number	Li-Ion Battery			70-minute		Flow Rate		Cartridges per Battery Charge		- Weight
	Quantity	Voltage	mAh	Charger	Pressure	High	Low	High Speed	Low Speed	Weight
596-A	1	20 V*	1500	120 V/60 Hz	10,000 psi (690 bar)	6 oz/min (170 g/min)	4 oz/min (113 g/min)	13	15	6.3 lb (2.9 kg)
596-B	2									
596-C	1			230 V/50 Hz						
596-D	2									

^{*}Maximum initial voltage without workload

Accessories

Mobile Charger	Carrying Strap	20 V Li-Ion Battery	Pressure Relief Valve	Bulk Loader Fitting	
343289	339812	343291	340338	322610	



1057 Red Ventures Drive Suite 100

Fort Mill, SC 29707

Toll Free U.S.: 866-4-Alemite
Toll Free Canada: 800-267-8022
International: 803-802-0001
Fax U.S.: 800-648-3917
Fax Canada: 800-267-2880
Fax International: 803-802-0192

www.alemite.com

Alemite® is a registered trademark of Alemite LLC