

OIL PUMPS

Pneumatic RAM - Portable

Alemite's Portable RAM Pump provides fast, quiet and efficient operation, and is recommended for use with gear oils.



FEATURES:

- 4 gallon per minute delivery (SAE 140 gear oil, 150 psi)
- Meets OSHA noise requirements (85dB)
- 3" diameter air motor
- Built in control valve holster, to keep hose and handle safely off of floor
- Steel dolly with durable casters
- Dispensing valve (included) designed for hard to reach areas, such as vehicle rear axles
- Easy serviceability
- 1/4" air inlet

INCLUDES:

- Drum Cover (338145)
- Control Valve (7492)
- 5 1/2' Material Hose (317813-5F)
- In line Electronic Meter (3679)
- Steel Dolly (316315-5)

Product #	Air Inlet	Drum Size	Pump Ratio	Delivery	Bare Pump	Weight
9961-1	1/4" NPTF(f)	16 gallon/120 Lb.	5:1	4 gpm	9968-A	40 Lb.

Pneumatic - Standard Duty

Alemite H-Pumps are designed for medium pressure industrial applications, featuring exceptional reliability and service life.



FEATURES:

- 2 7/16" diameter air motor
- Handles 10, 20 and 30W oils
- Will mount to 1 1/2" suction tube from remote tank
- Double toggle air valve trip mechanism prevents binding or stalling
- Corrosion resistant chrome finish on piston rods reduces packing wear
- Center flow, micro-lapped high pressure air valve provides very long life
- Self aligning, heavy acme threads provide safely locked linkage
- Requires appropriate downtube

343086 PACKAGE INCLUDES:

- 4:1 ratio Pump (8568-A4)
- Drum Dolly (316315-5)
- Electronic Meter (3673)
- 16 gal. Cover (338977)
- 7' Material Hose (317813-7)
- Filter/Regulator (7936)

Product #	Drum Size	Material Inlet	Material Outlet	Pump Ratio	Delivery	Bung Adapter	Weight
8568-A4	Stub	1 1/2" NPTF(f)	3/8" NPTF(f)	4:1	3 gpm	326750	14 Lb.