

INDUSTRIAL LUBRICATION FITTINGS

VENTS

Vents

Alemite Vents are used with transmissions, speed reducers, axles, gear housings and similar applications. The vent is placed above normal lubrication level to allow air to escape when internal pressure rises.

| Product # | Thread | Opening Pressure |
|-----------|---|-------------------------------|
| 300805 | 1/8" PTF SAE Short | Felt filter |
| 304810 | 1/8" PTF SAE Short | 1-3" water |
| 324970 | Drive 3/8". Designed as 0.374±0.000-0.003 drive. Use 0.368" drill or U drill. | 6-12" water, 0.25 to 0.43 psi |
| 131000-T | 1/8" PTF SAE Short | 12" water max |
| 327240 | 1/8" PTF SAE Short | 1 to 1-1/2 psi |
| 330766 | 1/8" PTF SAE Short | 2-1/2 to 4 psi |
| 369622 | 1/8" PTF SAE Special Short | 2-1/2 to 4 psi |
| 369602 | 1/8" PTF SAE Short | 1 to 2 psi |

FEATURES:

- Exceeds 72 hour salt spray test
- Trivalent zinc plating
- Vent opens at designated pressure (see table)
- Helps to prevent fluid leakage
- Special cap prevents water or dirt from entering

