

# OIL & GREASE EQUIPMENT FROM ALLUBE LTD

## AIR OPERATED OIL PUMPS

F0021400A - 3.5:1 175mm  
F0021402A - 3.5:1 940mm



"Pro + Silent" double acting oil transfer with high performance and durability and soundproof protective structure. The 3.5:1 can pump medium viscosity oils over short to medium distance.

- 21.5 lpm flow rate
- 2" BSP bung adaptor for stable drum/wall mounting
- 1/4" F air inlet / 3-8 bar
- 5.5:1 pumps also available with 175mm & 940mm pipes

FROM £241.56



## AIR OPERATED GREASE PUMPS

F00216050 - 470mm  
F00216060 - 730mm  
F00216070 - 940mm



Efficient double acting grease transfer with the "P60:1 Booster" ensuring high performance and durability and soundproof structure. For high pressure pumping over short & long distance.

- 60:1 ratio
- 4-8 bar air pressure
- 1/4" F air inlet
- 130-160 lpm air consumption
- For the following drum sizes: 12.5kg, 50kg and 180kg

FROM £279.99



## AIR OPERATED MOBILE OIL KIT

CTS2112 - 3.5:1 205L  
5.5:1 & 60L versions available



3.5:1 ratio air operated oil pump in a drum kit assembly, with trolley for easy movability. Kit comes complete with K400 flexi spout nozzle with integrated meter and 2m dispensing hose.

- 21.5 lpm flow rate
- 2" BSP bung adaptor for connecting to a 205L drum
- 1/4" F air inlet
- 3-8 bar air pressure
- 940mm suction pipe

PRICE £745.21



## AIR OPERATED GREASE PUMP KIT

CTS3001  
Suitable for 12.5kg drum



Ready to dispense air operated grease pump kit for use with a 12.5kg drum. Assembly c/w P60:1 Booster pump, 4m del hose, grease gun with straight swivel, drum cover and follower plate.

- 60:1 ratio
- 4-8 bar air pressure
- 1/4" M BSP x 1/4" F BSP
- 130-160 lpm air consumption
- 285mm drum cover with gun support & 270mm plate

PRICE £392.48



## S/S ROTARY HAND PUMP

F00332500 - Open spout  
Version with hose available



Self priming rotary hand pump with s/s casing for reliability and durability. Rolling hand grip for smooth operation and grooved locking mechanism to stop it spinning on the drum when in use.

- 380ml per rev max flow rate
- 2" M BSP drum connector
- Suction downtube
- 'S' type spout for dispensing straight into an oil jug
- Quality constructed internals

PRICE £104.31



## AIR OPERATED MOBILE GREASE KIT

CTS3002 - 12.5kg  
50kg drum version available



P60:1 air operated mobile grease pump kit, with two wheel trolley for easy manoeuvring. Mobile kit c/w 4m delivery hose, grease gun with straight swivel, drum cover and follower plate.

- 60:1 ratio
- 4-8 bar air pressure
- 1/4" M BSP x 1/4" F BSP
- 130-160 lpm air consumption
- 285mm drum cover with gun support & 270mm plate

PRICE £460.74



Prices based on current RRP's



# OIL & GREASE EQUIPMENT FROM ALLUBE LTD

## OPEN OIL HOSE REEL

HA60101200 - 1/2" x 10m

Closed, bare & other lengths available

Automatic open reel for high pressure dispensing & heavy duty conditions. C/w ratchet to prevent lockup when hose's extended, 4 way rollers to assist unrolling and hose stop for locking length.

- 10m hose length
- Adjustable arm brackets
- 1/2" M BSP Swivel inlet
- 1/2" M BSP 60o Cone Seat
- Closed reels, bare reels and other length hoses available

PRICE **£347.79**



## K500 PRE-SET NOZZLE

68700B  
Rigid Spout

Pre-set oil dispensing nozzle for lubricating oils. C/w auto spout that shuts off when quantity's been dispensed & trigger operation to prevent any accidental overfill. Pre-select range 0.1 - 99.9 ltrs.

- 30 lpm flow rate
- Viscosity up to 2000cSt
- +/-0.5% accuracy
- 1/2" F BSP Swivel
- 70 bar max pressure
- 4 x AA batteries - 1.5v

PRICE **£422.71**



## K400 NOZZLE METER

F00984010 - Flexi Spout

Rigid & no spout also available

Oil dispensing nozzle with integrated digital meter for measuring quantity dispensed. Trigger lock to prevent accidental overfill and flexi spout with an automatic non-drip valve to minimise mess.

- 30 lpm flow rate
- Meter accuracy +/- 0.5%
- 70 bar max pressure
- Oil up to 2000 cSt
- 1/2" F BSP Swivel c/w mesh strainer

PRICE **£205.24**



## GREASE CONTROL NOZZLE

F20605000

Rigid spout c/w 4 jaw coupler

A grease control nozzle from Piusi for the dispensing point of an air operated grease pump installation. Spring type pistol trigger operation which comes with a rigid spout with 4 jaw connector.

- Rigid spout c/w 4 jaw coupler
- 470 bar max pressure
- 1/4" F BSP inlet connection
- Straight and Z swivels available as inlet accessories

PRICE **£35.85**



## CTS ECONOMY LEVEL ALARM

SWS1022 - Tank alarm only

SWS1038 - High viscosity probe

Battery powered entry level tank alarm to indicate high or low level. Battery lasts approx. 72hrs in full alarm mode. Comes with 4 mounting lugs & 3 stickers to name LED - high, low & blank.

- Flashing LED & 90db alarm
- Test & alarm mute functions
- Weatherproof IP55 enclosure
- Probe for waste oil tanks - 5m PVC cable, 60oC max temp & 1 1/2" F BSP brass cap

TOTAL **£125.89**



## MT PROFIL FLOAT GAUGE

OAB3304 - 4ft

Gauges for other heights available

Simple and cost effective float operated clock gauge for quick and clear identification of approx. tank contents. Small mechanical display showing tank level as Empty, 1/4, 1/2, 3/4, Full.

- 4ft / 1219mm tank height
- 1 1/2" M BSP fitting for easy top mounting onto tank
- Other gauges available in other sizes depending on tank/drum height

PRICE **£12.19**



Prices based on current RRP's

